

WSI-05.08-TA2Z




Inductive proximity sensor

DESIGN FAMILY CUSTOM

- Increased distance
- Miniature F1

Product photograph to follow


DIMENSIONS



PINOUT



OUTPUT



CERTIFICATIONS



Technical data			
Electrical features		Mechanical features	
Supply Voltage	10–30 VDC	Form Factor	M5
No-Load Current	≤10 mA	Dimensions (mm)	Ø5×25
Max Output Current	≤200 mA	Mounting	Flush
Voltage Drop	≤2 V	Material (body)	304 Stainless
Output Circuit	PNP	Material (Face)	High Temp Epoxy
Output Normal State	N.O.	Coating	ACTIVSTONE
Switching Frequency	≤3kHz	Coating Type	Z
Sensing performance		Connection	
Rated Sensing Distance (Sn)	0.8mm	Cable Sheath Outer	ACTIVFLEX TUBULAR
Correction Factors (Steel=100%)	Steel 100% Stainless St 80%, Al 50%	Cable Length	2m
Factor 1	NO	Cable Exit Direction	Straight
Hysteresis	≤10%	LED on Sensor	YES
Repeat Accuracy	0.03 mm	Environmental	
SENSING TARGETS PRACTICALITY	Steel Only	Operating Temperature	-25...+70°C
		Protection Class	IP67