WSI-1602HL-FABZ

WSI-1602HL-FABZ


Mini Flat Pack Inductive Sensor

DESIGN FAMILY **HYPERLIFE**


- 8 x 16 x 4.7mm with M3 mounting hole
- 2mm Sensing Range
- PNP, N.O.
- Standard Temp +75C
- HYPERFACE
- 500mm FLEXLINC SPRINGLOC Armor over PTFE
- M8 Metal Connector
- Red LED on Sensor Head



DIMENSIONS




PINOUT



M8

OUTPUT



CERTIFICATIONS

Technical data

Electrical features	
Supply Voltage	9–30 VDC
No-Load Current	≤12 mA
Max Output Current	<100 mA
Voltage Drop	<2 V
Output Circuit	PNP
Output Normal State	N.O.
Switching Frequency	5 kHz
Sensing performance	
Rated Sensing Distance (Sn)	2 mm
Correction Factors (Steel=100%)	Steel 100 %, St Steel 75 %, Al 50 %
Hysteresis	2–20%
SENSING TARGETS PRACTICALITY	Steel, Aluminum
Mechanical features	
Form Factor	Mini Flat Pack
Dimensions (mm)	16×8×4.7
Mounting	Flush
Material (body)	Alloy
Material (Face)	HYPERFACE
Coating Type	Z

Connection	
Connector Type	M8 3P
Connector Material	FEP over METAL
Cable Sheath Inner	PTFE
Cable Sheath Outer	FLEXLINC SPRINGLOC STAINLESS
Cable Length	0.5m
Cable Exit Direction	Straight
LED on Sensor	YES
LED on Connector	NO
Connector LED Color	NONE
Environmental	
Operating Temperature	-25…+75°C
Protection Class	IP67

© Weld Dynamix, Inc. Right to change reserved